

WI-FI

- 2.4 GHz 802.11 b/g/n Radio, RP-SMA standard antenna connector
- Authenticated local access to automation network through PC, tablet, smartphone. Internet connectivity via VPN tunnel through our gateway and isolation from installation network (WAN)
- Internet connectivity through installation access point or mobile hotspot
- Optional SSID (guest) isolated from the automation network, dedicated to Internet access

SOUND ASSISTANCE

- Acoustic signaling of Sevio Router status

CASE

- Metallic case: S235JR Steel
- Dimensions: 121(H) x 40(W) x 156(D) mm

MOUNTING

- DIN rail mounting with wide, 38 mm, clip

POWER SUPPLY

- Wide 8-30 V DC power supply with polarity reversal protection
- Plug-in connector with 3,81 mm terminal block

USB 2.0

- Mobile Broadband Modem connectivity
- USB Flash drive (included) for offline configuration

WAN

- DHCP Client (default) or static IP, configurable via Sevio Portal
- Internet connection via Customer network
- 1 Ethernet RJ45 10/100/1000 Mbit/s port

FIREWALL

- Total isolation between installation network (WAN) and automation network (LAN)
- No IP address conflicts between installation network (WAN) and automation network (LAN)

LAN

- DHCP Server configurable through Sevio Portal
- Up to 253 devices with additional switches
- 4 Ethernet RJ45 10/100/1000 Mbit/s ports
- Full Internet access via VPN tunnel through our gateway
- Auto MDI/MDIX



WAN connectivity	✓
Wi-Fi connectivity	✓
Mobile connectivity (through optional modem)	✓
Sound assistance	✓
WAN	1 X RJ45 10/100/1000 Mbit/s
Firewall	✓
Switch	Gigabit

Wi-Fi	✓
Remote configuration	✓
USB 2.0	✓
VPN protocols	SSTP/L2TP/PPTP/OpenVPN
DIN Clip	✓
Power Supply	8-30 V DC with polarity reversal protection
Warranty	24 months

Sevio S.r.l.

Via dei Caniana 6/a | 24127 BERGAMO | Ph: +39 035 0514333 | info@sevio.it

sevio.it