

SEVIO

basic

Wi-Fi

- 2.4 GHz 802.11 b/g/n Radio, RP-SMA standard antenna connector
- Access point mode - Authenticated local access to LAN (automation network) through PC, tablet, smartphone, isolated from installation network.
LAN Internet connectivity configurable from Sevio Portal
- Client mode - Internet connectivity through installation site Access point or mobile hotspot

SOUND ASSISTANCE

- Acoustic signaling of Sevio Router status

ENCLOSURE

- S235JR Steel - IP20
- Dimensions: 121(H) x 40(W) x 156(D) mm
- Weight: 600 g

MOUNTING

- Standard DIN rail mounting 35 mm

POWER SUPPLY

- Wide 8-30 Vdc with polarity reversal protection
- Plug-in connector 3,81 mm with terminal block



WAN

- DHCP Client (default) or static IP configurable via Sevio Portal
- Internet connection via Customer network
- 1 Ethernet RJ45 10/100 Mbit/s port

FIREWALL

- Isolation between installation network and automation network: network segmentation, no IP address conflicts
- 4 Levels of User Management
- Intra-LAN: VPN communication between automation network installed in different places

LAN

- DHCP Server configurable through Sevio Portal
- 4 Ethernet RJ45 10/100/1000 Mbit/s ports with integrated switch
- Internet access configurable through Sevio Portal
- Auto MDI/MDIX
- Up to 253 devices reachable with additional switches

USB 2.0

- Data SIM connectivity via Sevio M100
- USB Flash drive FAT32 for offline configuration

WAN connectivity	✓
Wi-Fi connectivity (Client mode)	✓
Mobile connectivity (optional M100)	✓
Sound assistance	✓
WAN	1x RJ45 10/100/1000 Mbit/s
Firewall	✓
Switch	Gigabit

Wi-Fi	✓
Remote configuration	✓
USB 2.0	✓
VPN protocols	SSTP / OpenVPN
DIN Clip	✓
Power Supply	8-30 Vdc with polarity reversal protection
Warranty	24 Months

Sevio S.r.l.

Via della Pusterla, 36 - 20826 Misinto (MB) - IT

+39 02 97070785 info@sevio.it https://sevio.it/