

SEVIO One

USB 2.0

- Mobile Broadband Modem connectivity
- USB Flash drive (included) for offline configuration

MOUNTING

- DIN rail mounting with wide, 22 mm, clip

WAN

- DHCP Client (default) or static IP, configurable via Sevio Portal
- Internet connection via Customer network
- 1 Ethernet RJ45 10/100 Mbit/s port

CASE

- Metallic case: S235JR Steel
- Dimensions: 90(H) x 23(W) x 105(D) mm

FIREWALL

- Total isolation between installation network (WAN) and automation network (LAN)
- No IP address conflicts between installation network (WAN) and automation network (LAN)

POWER SUPPLY

- Wide 8-30 V DC power supply with polarity reversal protection
- Plug-in connector with 3,81 mm terminal block



LAN

- DHCP Server configurable through Sevio Portal
- Up to 253 devices with additional switches
- 1 Ethernet RJ45 10/100 Mbit/s port
- Full Internet access via VPN tunnel through our gateway
- Auto MDI/MDIX

WAN connectivity	✓
Wi-Fi connectivity	...
Mobile connectivity (through optional modem)	✓
Sound assistance	...
WAN	1 X RJ45 10/100 Mbit/s
Firewall	✓
Switch	...

Wi-Fi	...
Remote configuration	✓
USB 2.0	✓
VPN protocols	SSTP/L2TP/PPTP/OpenVPN
DIN Clip	✓
Power Supply	8-30 V DC with polarity reversal protection
Warranty	24 months

Sevio S.r.l.

Via dei Caniana 6/a | 24127 BERGAMO | Ph: +39 035 0514333 | info@sevio.it

sevio.it