



Requirements Internet Connection

- Sevio Router only originates outbound connections, it does not require public IP assignment or static NAT mapping.
- Sevio Router must be allowed to originate SSTP (Port **443/TCP**) and OpenVPN (Ports **1194/TCP** and **1194/UDP**) connections to Sevio infrastructure - requirement also applies to connections via Data SIM.
- VPN Concentrators IP addresses are dynamic in order to provide traffic load-balancing, geographical proximity and DoS (Denial of Services) prevention and mitigation. Responds at FQDN ***.sevio.it**, the specific FQDN **concentrators.sevio.it**, includes all IP Addresses available for routers connection.
- To assure the better service over time, also consider allowing Sevio IP addresses block **45.66.80.0/22**.
- If filters on the MAC addresses are enabled, the WAN MAC Address used in case of wired connection or the WLAN MAC Address used in case of Wi-Fi connection should be shared with installation site IT manager, MAC addresses can be found on Sevio Portal or in the Registration Sheet.
- Sevio Router does not require a DNS resolver.
- Sevio Router can be installed behind HTTP/HTTPS Proxy-Server if it supports Transparent Mode (or if Proxy-Server does not require authentication).
- Sevio Router supports 802.11b / g / n Wireless (Wi-Fi) networks with WPA / WPA 2 PSK encryption in 2.4 GHz band.

Installation requirements		
Wired Connection	Wi-Fi connection	
	SSID:	
	Password:	
DHCP Client	Static IP	
	IP Address:	
	Netmask:	
	Gateway:	
Mobile - Data SIM	APN:	PIN:
Access Internet enable		
HTTP/HTTPS Proxy	IP Address:	Port: